


Casters & Wheels

General Duty - 4000 Series (Capacity to 300 lbs.)



Wheel Dia./Width	Wheel Material	Load Cap. (LBS)	Swivel/Rigid	Part #
4" x 1-1/4"	Soft Rubber	200	S	14-4040-01-SR

- Top Plate Size - Swivel - 1-3/16" x 2-3/8" Rigid - 1-3/16" x 1-3/4"
- Bolt Hole Spacing - Swivel - 1-3/4" Rigid - 13/16" x 1-3/4"
- Attaching Bolt Size - Swivel - 3/16" Rigid - 11/64"

Light/Medium Duty - 5000 Series (Capacity to 350 lbs.)

- Top Plate Size - 2-1/2" x 3-3/4"
- Bolt Hole Spacing - 1-3/4" x 2-7/8" to 3"



Attaching Bolt Size - 5/16" Wheel Dia./Width	Wheel Material	Load Cap. (LBS)	Swivel/Rigid	Part #
3" x 1-1/4"	Steel	250	S	14-5030-01-STL
3" x 1-1/4"	Mirage	155	S	14-5030-01-Mir
3" x 1-1/4"	Mirage	155	S-Total Lock Brake	14-5030-01-Mir-SWB
3" x 1-1/4"	Mirage	155	R	14-5030R-01-Mir
4" x 1-1/4"	Steel	300	S	14-5040-01-STL
4" x 1-1/4"	Hard Rubber	255	S	14-5040-01-HR
4" x 1-1/4"	Hard Rubber	255	R	14-5040R-01-HR

Mir - Mirage Wheel

- Special formula rubber tread-it cannot mark.
- Tough polyolefin core helps absorb shocks.
- Tread mechanically bonded to the core.
- Easy-Glide ball bearings-not the press-in type.
- Rolls like rubber, acts like polyurethane.
- Perfect for most institutional and industrial uses.
- This series is NSF Listed. Please call for information.



Hard Rubber Wheel

- Made of high impact molded rubber composition.
- Higher load capacity soft rubber.
- Tread durometer is 75 ± 5(SHORE D)
- Good mobility and durability.
- This series is NSF Listed, Please call for information.



Phenolic Wheels

- Phenolic resin and macetated fabric combined to resist hard
- Provides superior floor protection.
- Quieter operation than steel with comparable capacity.
- Resistant to oils and gasoline.
- High-Temperature compositions available, (call for informati
- Roller bearings provide consistent, smooth rolling.
- This series is NSF Listed. Please call for information.



Medium Heavy Duty - 6000 Series (Capacity to 900 lbs.)



Wheel Dia./Width	Wheel Material	Load Cap. (LBS)	Swivel/Rigid	Part #
4" x 2"	Phenolic	700	S	14-6640-01-PHN
4" x 2"	Phenolic	700	R	14-6640R-01-PHN
5" x 2"	Phenolic	800	S	14-6650-01 PHN
5" x 2"	Phenolic	800	R	14-6650R-01 PHN
5" x 2"	Phenolic	800	S	14-6650-01-PHN-TLB
5" x 2"	EZ Roll Poly	1050	S	14-27SW5J0JU04I7YY
5" x 2"	Phenolic	800	Wheel Only	14-PHN5M7
6" x 2"	Rubber/ Cast Iron	440	S	14-6660-01 RCI
6" x 2"	Rubber / Cast Iron	440	R	14-6660R-01 RCI
8" x 2"	Steel	900	S	14-6680-01-STL
8" x 2"	Phenolic	900	S	14-6680-01-PHN-AMP
8" x 2"	Phenolic	900	R	14-6680R-01-PHN-AMP
8" x 3"	Solid Poly	275	R	14-6680-W-01-PBB-AFR

- Top Plate Size - 4" x 4-1/2"
- Bolt Hole Spacing - Slotted - 2-5/8"x 3-5/8" to 3" x 3"
- Attaching Bolt Size - 3/8"

Wheels



Wheel Dia./Width	Bore	Load Cap. (LBS)	Part #
8" x 1.75"	1/2" (1-38" offset)	110	14-875-OFBB1/2
8" x 1.75"	5/8"	110	14-875-58HD
8" x 2"	3/4" Plain Bore	675	14-90-06-008
10" x 1.75"	5/8"	150	14-110-58-OF-HD
10" x 1.75"	5/8"	150	14-110-58-HD

Rubber Tread Cast Iron Center Wheels



Wheel Dia./Width	Bore	Load Cap. (LBS)	Part #
8" x 2"	3/4"	500	14-RCI-8M7

Cushion, rubber tread with a strong cast-iron center / roller bearing / zerk fitting in hub / full floor protection and highly shock absorbent.

Don't see the Caster or Wheel you need?

Just ask and we will be happy to give a quote on all your wheel and caster needs.